

mody

mody

MS SERIES

WET PIT

PORTABLE

2", 3", 4", 6", 10"
(50, 75/80, 100, 150, 250 mm)
DISCHARGE SIZES

2 HP - 20 HP
1.5 kW - 15 kW



**ELECTRIC
SUBMERSIBLE
SEWAGE PUMPS**

mody
Pumps

mody

MS SERIES SUBMERSIBLE PUMPS

2" to 10" / 50 to 250 mm
DISCHARGE SIZES

WET PIT

PORTABLE

MOTORS:

2 POLE 2-3 HP / 1.5-2.2 kW
4 POLE 3-20 HP / 2.2-15 kW
6 POLE 12-14 HP / 9-10.5 kW
208/230/400/460/575/1000V
50/60Hz

FLOWS to 4,000 US GPM / 15,000 LPM

HEADS to 80 FT / 25 MTS

CHANNEL IMPELLER

SEMI-OPEN IMPELLER

CUTTER VERSION



mody

FEATURES

- ◆ **High Efficiency Motors**
 - ▶ Ip 68 Enclosure
 - ▶ Class H (180°C) Insulation System
 - ▶ Klixon Type Thermal Protection In Windings
 - ▶ Water Dam Cable Entry Gland System
 - ▶ Unique Stainless Steel Cable Sheathing System
- ◆ **Tandem Mechanical Seals**
 - ▶ Tungsten Carbide Seal Faces
 - ▶ Stainless Steel Fasteners And Springs
 - ▶ Moisture Sensor
- ◆ **Cast Iron Materials Of Construction**
- ◆ **Optional Stainless Steel Materials Of Construction**
- ◆ **3" (75/80 mm) / 4" (100 mm) Solids Handling Capability**
- ◆ **Easy Retrofit To Flygt® Installations**

CROSS-REFERENCE TABLE

MODY®	FLYGT®	SIZE	HP/kW	POLES
MS121	3068 MT	2"-50mm	2-1.5	2
MS231	3085 MT	3"-75/80mm	3-2.2	2
MS232	3085 MT	4"-100mm	3-2.2	4
MS252	3102 MT	4"-100mm	5-3.7	4
MS480	3127 MT	4"-100mm	7.5-5.5	4
MS481	3127 MT	4"-100mm	10-7.5	4
MS482	3127 MT	6"-150mm	10-7.5	4
MS483*	F 3127	6"-150mm	10-7.5	4
MS6150	3152 LT	10"-250mm	14-10.5	6
MS6152	3152 MT	6"-150mm	15-11	4
MS6202	3152 MT	6"-150mm	20-15	4

* Cutter Pump

mody
Pumps

Mody Pumps® Inc.

2166 Zeus Court, Bakersfield, CA 93308, USA
Tel.: (661) 392-7600 • Fax: (661) 392-7601
<http://www.modypump.com>
E-mail: sales@modypump.com